REVISIONS ZONE LTR DESCRIPTION DATE APPROVED METAL STAMP PER NOTE I NOTES: .04 X 45° TYP I. MARK AS SPECIFIED IN LOCATION SHOWN .005.015 R. WITH LA -3/16 HIGH FIGURES THE FOLLOWING: a) THE NAME "ALLISON" FOLLOWED BY THE TOOL NUMBER AND LAST CHANGE LETTER. N VENDOR NAME OR TRADEMARK. 2. CADMIUM PLATE PER AMS 2400 DIM. MUST BE MET AFTER PLATING PROPELLER SHAFT ASSY (REF) AMS 2400 LOCAL SPECIL DEFT DRAWGING PRACTICE SURFACE TEXTURE SCREW THREADS BREAK SHARP EDGES.080 U.S. GENERAL SPECIFICATIONS APPROVALS ALLICON DIVISION
GENERAL MOTORS COMPORATION
INDIANAPOLIS, INDIANA UNLESS OTHERWISE SPECIFIED CHECKED ROM SAUGE TOL ON ANGLES = /" TOL ON 3 PLACE DECIMALS ± 0/0 5AUG 68 TOL ON 2 PLACE DECIMALS ± 02 4-PLACE DECIMAL DIMENSIONS WITHOUT TOLERANCES AFE BASIC CHF. DR. PUTS/CY DRIFT-PROP SHAFT FNGR 1 ASSEMBLY ENGR. 2 A. YOURNOVICE 16 JA 68 ENGR. 3 & J.R. 26 Jol 66 SAE 4140 APPLICATION: SEE SEPARATE PARTS LIST MODEL # MET USAGE FINAL RUN SIZE | CODE IDENT | DWG. No. HEAT TREAT AND HARDNESS REVIEW APPROV Rc 36-40
SURFACE TREAT. INSPECTION
NOTED 98983 73342 USED ON ENGINE MODELS 250 SERIES ---